



4MLT LIGHTING TOWER

GENSET

- ◆ Multi-directionally adjustable and tiltable floodlights
- ◆ 5 sections vertical tower 7 m, 340° rotatable
- ◆ Galvanized mast
- ◆ 80 um powder coating
- ◆ .Forklift pockets for effective handling, both the rear and the sides
- ◆ Control panel alarms for engine protection and fuel level indicator
- ◆ Circuit breaker for electrical protection against overload
- ◆ External emergency stop button
- ◆ Wind stability up to 80 km/h
- ◆ 4 height adjustable stabilizers



Gas, oil & mining
operations



Construction
& work sites



Special
events



Emergency



max height
7 m



720kg



rotation
340°



Fuel tank
100L 0.58L/h



Technical Data

GENERAL

Model	4MLT1200-7
Minimum dimensions	1700*1300*2586mm(LxWx H)
Maximum dimensions	2460*2100*7270mm(LxWxH)
Total weight	720kg
Fuel tank	100 L
Load on a 40"HC	21 units disassembled or 9 units assembled



OPERATIONAL DATA

Engine	Kubota Z482
Alternator	5.5kW,IP23,220V/1230V,AVR
Operating hours with full load	80 hrs
Operating hours with full lights on	170 hrs
Mast Lifting	Manual
Max Height	7.27 m
Mast Rotation	340°
Lights	4 x350W LED
Lighting coverage	6500m ² at 5 lux
Wind Rating	80km/h



OPTION

Lights	4 x 400W LED
Mast Lifting	Electric